



Specification

Nominal Voltage	12V	
Nominal Capacity(20HR)	0.8AH	
Dimensions	Length	96 ± 1mm (3.78 inches)
	Width	25 ± 1mm (0.98 inches)
	Container Height	62 ± 1mm (2.44 inches)
	Total Height (with Terminal)	62 ± 1mm (2.44 inches)
Approx Weight	Approx 0.35 kg (0.77lbs)	
Terminal	/	
Container Material	ABS	
Rated Capacity	0.80 AH/0.04A	(20hr, 1.80V/cell, 25°C/77°F)
	0.74 AH/0.074A	(10hr, 1.80V/cell, 25°C/77°F)
	0.67 AH/0.134A	(5hr, 1.75V/cell, 25°C/77°F)
	0.588 AH/0.196A	(3hr, 1.75V/cell, 25°C/77°F)
	0.493 AH/0.493A	(1hr, 1.60V/cell, 25°C/77°F)
Max. Discharge Current	12A (5s)	
Internal Resistance	Approx 150mΩ	
Operating Temp. Range	Discharge	-15 ~ 50°C (5 ~ 122°F)
	Charge	0 ~ 40°C (32 ~ 104°F)
	Storage	-15 ~ 40°C (5 ~ 104°F)
Nominal Operating Temp. Range	25 ± 3°C (77 ± 5°F)	
Cycle Use	Initial Charging Current less than 0.24A. Voltage 14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
	Standby Use No limit on Initial Charging Current Voltage 13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	CT series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	

Applications

- ◆ All purpose
- ◆ Uninterruptable Power Supply (UPS)
- ◆ Electric Power System (EPS)
- ◆ Emergency backup power supply
- ◆ Emergency light
- ◆ Railway signal
- ◆ Aircraft signal
- ◆ Alarm and security system
- ◆ Electronic apparatus and equipment
- ◆ Communication power supply
- ◆ DC power supply
- ◆ Auto control system



Constant Current Discharge (Amperes) at 25 °C (77°F)




F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	1.48	1.07	0.896	0.766	0.614	0.473	0.386	0.236	0.180	0.148	0.125	0.109	0.086	0.072	0.040
1.80V/cell	1.89	1.28	1.02	0.866	0.680	0.515	0.416	0.251	0.189	0.155	0.131	0.113	0.090	0.074	0.040
1.75V/cell	2.24	1.44	1.13	0.943	0.726	0.547	0.438	0.262	0.196	0.160	0.134	0.116	0.092	0.076	0.040
1.70V/cell	2.54	1.61	1.24	1.02	0.773	0.575	0.459	0.272	0.202	0.164	0.138	0.119	0.093	0.077	0.041
1.65V/cell	2.80	1.74	1.33	1.09	0.814	0.599	0.475	0.280	0.207	0.168	0.141	0.121	0.095	0.078	0.042
1.60V/cell	3.02	1.88	1.42	1.16	0.856	0.624	0.493	0.289	0.212	0.172	0.144	0.124	0.097	0.080	0.042

Constant Power Discharge (Watts) at 25 °C (77°F)


F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	2.81	2.05	1.73	1.49	1.20	0.931	0.765	0.470	0.359	0.296	0.252	0.219	0.175	0.146	0.080
1.80V/cell	3.55	2.43	1.97	1.68	1.33	1.01	0.821	0.498	0.376	0.310	0.262	0.228	0.180	0.150	0.081
1.75V/cell	4.16	2.73	2.16	1.82	1.41	1.07	0.862	0.517	0.388	0.319	0.268	0.233	0.185	0.153	0.081
1.70V/cell	4.69	3.02	2.36	1.96	1.50	1.12	0.901	0.537	0.400	0.326	0.274	0.238	0.187	0.155	0.083
1.65V/cell	5.11	3.23	2.50	2.07	1.57	1.16	0.929	0.551	0.409	0.332	0.280	0.242	0.189	0.156	0.083
1.60V/cell	5.45	3.44	2.65	2.19	1.63	1.20	0.959	0.566	0.417	0.339	0.284	0.246	0.193	0.159	0.084

Dimensions


Terminal Unit: mm [inches]




Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Effect of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



Self Discharge Characteristics



- A** No supplementary charge required (Carry out supplementary charge before use if 100% capacity is required.)
- B** Supplementary charge required before use. Optional charging way as below:
1. Charged for above 3 days at limited current 0.25CA and constant voltage 2.25V/cell.
2. Charged for above 20 hours at limited current 0.25CA and constant voltage 2.45V/cell.
3. Charged for 8-10 hours at limited current 0.05CA.
- C** Supplementary charge may often fail to recover the capacity. The battery should never be left standing till this is reached.

Sales Office

Sweden

Celltech AB,
 Äggelundavägen 2, 175 62 Järfälla, Sweden
 TEL: +46 8445 7870
 FAX: +46 8445 7878
 E-mail: order@celltech.se
 www.celltech.se

Finland and Baltic countries

Celltech Oy
 Höylätamitie 11A, 00380 Helsinki, Finland
 TEL: +358 (0)207 999 640
 FAX: +358 (0)207 999 641
 E-mail: info@celltech.fi
 www.celltech.fi

Denmark

Celltech A/S
 Rugmarken 9B, 3520 Farum, Denmark
 TEL: +45 7025 2201
 FAX: +45 7025 2202
 E-mail: info@celltech.dk
 www.celltech.dk